# To Install Hanger | Models 338, 339



#### **Instructions and Information**

#### **To Install Hanger:**

- Start by inserting the end into the left side panel. There are two holes, insert into the upper one. (Fig. 1)
- Bring other end of the hanger around the back of the feeder as shown. (Fig. 2)
- Place other hanger end into the single hole found on the right side panel. Important Note: To insert properly, you will have the hanger in a down position, pointing to the back of the feeder as shown. (Fig. 3)
- Lift the hanger into the upright position. You will notice the end of the hanger on the left side panel, springing out from the lower hole as indicated. This will lock the hanger in an upright position. (Fig. 4)

### To Install Weather Vane/Chimney:

- Insert bottom shaft of weather vane/chimney through top of roof peak. Attach screw and locking key to shaft end. Important Note: Make sure you attach screw and locking key to the shaft end exactly as shown. (Fig. 5)
- Fill your feeder with your favorite seed mix. Position roof peak as shown and gently press down so the locking key inserts into the cross beam inside the feeder. While still pressing down, gently turn the weather vane/chimney clockwise, 3/8 of a turn, DO NOT FORCE OR DAMAGE MAY RESULT. Your roof peak should now be latched. (Fig. 6)

## Adjusting your Squirrel-Proof Settings:

 Depending on the species and age of squirrels in your area, you will want to experiment with different settings. To increase tension, lower the adjustment pin. To decrease tension, raise the pin to a higher slot position. (Fig. 7)

#### To Mount Pole/Post Adapter:

- To mount pole: Use standard 3/4" pipe to pole mount your feeder. If you desire to place your feeder on a 4' x 4' wood post, use the included adapter and screws.
- To use adapter: Place adapter on the post with downward slant on the adapter pointing in the direction you want your feeder to face. Use the four included screws to attach the bottom and place it on the adapter.

NOTE: The feeder should be level once mounted.













